

WATER SAFE®

RECOMMENDED HEATERS / A.S.S.E. 1060 CLASS I Enclosures

MODEL NO.	QTY.	HEATER		MODEL NO.	QTY.	HEATER
WS-3-NRS	One	RH-2-A		WS-4FM-NRS	One	RH-2-A
WS-3-NRS-S	One	RH-2-A		WS-4FM-OSY	One	RH-2-A
WS-3-OSY	One	RH-2-A		WS-4FM-OSY-FDC	One	RH-2-A
WS-3-OSY-S	One	RH-2-A				
WS-4-NRS	One	RH-2-A		WS-6FM-NRS	One	RH-2-A
WS-4-NRS-S	One	RH-3-A		WS-6FM-OSY	One	RH-2-A
WS-4-OSY	One	RH-2-A		WS-6FM-OSY-FDC	One	RH-2-A
WS-4-OSY-S	One	RH-3-A				
WS-6-NRS	One	RH-3-A		WS-8FM-NRS	One	RH-2-A
WS-6-NRS-S	One	RH-4-A		WS-8FM-OSY	One	RH-3-A
WS-6-OSY	One	RH-3-A		WS-8FM-OSY-FDC	One	RH-3-A
WS-6-OSY-S	One	RH-4-A				
WS-8-NRS	One	RH-4-A		WS-10FM-NRS	One	RH-3-A
WS-8-OSY	One	RH-4-A		WS-10FM-OSY	One	RH-3-A
WS-8-NRS-S	Two	RH-3-A		WS-10FM-OSY-FDC	One	RH-3-A
WS-8-OSY-S	Two	RH-3-A				
WS-10-NRS	Two	RH-3-A				
WS-10-NRS-S	Two	RH-3-A				
WS-10-OSY	Two	RH-3-A				
WS-10-OSY-S	Two	RH-3-A				

HEATER SPECIFICATIONS

G & C Model No.	Volts	Amps	Hertz	Watts	Phase
RH-2-A	120	6.7	60	800	Single
RH-2-B *	208	3.9	60	800	Single
RH-2-C *	240	3.3	60	800	Single
RH-3-A	120	9.2	60	1100	Single
RH-3-B *	208	5.3	60	1100	Single
RH-3-C *	240	4.6	60	1100	Single
RH-4-A	120	15.0	60	1800	Single
RH-4-B *	208	8.7	60	1800	Single
RH-4-C *	240	7.5	60	1800	Single
RH-5-A *	208	12.0	60	2500	Single
RH-5-B *	240	10.4	60	2500	Single
RH-6-A *	208	14.4	60	3000	Single
RH-6-B *	240	12.5	60	3000	Single
RH-7-A *	240	15.0	60	3600	Single

NOTE: * Consult factory for price and availability